



## ➔ Sticker (Self-Adhesive) Labelling Machines

### ➤ ABMA-40 - Semi Automatic Horizontal Sticker Labelling Machine



[Layout](#)



[E-Catalog](#)



[Video](#)

The Semi Automatic Horizontal Sticker Labelling Machine Model ABMA-40, is one of the most user friendly. Suitable for applying Wrap Around Labels on Cylindrical or Round Bottles with output Up to 40 Labels per minute depending on products and label size. Automatic The Machine is developed for use of the customers requiring lower rate of production for their round bottles/containers, where Automatic Labelling Machine are not economical. No Change Parts required for Label size and Product Size, the change over time is very less.

Machine is suitable for Labelling on Round Bottles, Jars, Tins, Cans, Containers and other round objects. It is capable of Labelling up to 40 units per minute depending on products and label size. Machine is Table Top Model and can be used in any packaging area with ease.

The Sticker Labelling Machine ABMA-40 has its own unique single point synchronised speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the machine. The System thus saves valuable time, avoiding machine

## BUILT-IN UNIQUE FEATURES :

- No Label Data Input/retrievals require for any Label Size
- No Change Parts for Product and Label size
- Virtually Maintenance free machine
- Easy to change label application height
- User Friendly Label Placing Adjustments
- Self Protected against Voltage Fluctuations
- Suitable for On-Line InkJet and Contact Coding System
- Suitable for Partial, Full Wrap Around and Overlap Labelling
- Built In A.C. Variable Frequency Drive System.
- Fully Stainless Steel finish Machine
- Refer Plug & Play Sticker Labelling UNIQUE FEATURES page for more details

## OPTIONAL FEATURES :

- Label Roll Empty - Machine Stop System with Alarm
- Missing Label in Roll - Machine Stop System with Alarm
- Option of Contact Coder, Hot Foil Coder, HP Cartridge Coder and Inkjet Coder with various speed range available.
- Low Compressed Air - Machine Stop with Alarm system for pneumatically operated coding system

## TECHNICAL SPECIFICATIONS :

Label Height :	8 mm to 70 mm Standard*
Label Length :	12 mm Minimum
Label Roll Dia. :	300 mm
Core Dia. :	75/76 mm
Gap Between two Labels :	appx. 3 mm
Product Size :	25mm to 90mm*
Electrical :	220 VAC Single Phase Power Supply (50/60 Hz)
Power :	1.2 Amp.
Capacity :	0.75 Kw
Speed :	Up to 40 Labels per minute depending on Product and Label Size.

\* Specification can be changed as per customers requirements

### Unique Features