



➤ Washing and Air Jet Cleaning Machines

☑ BAVC-60 - Automatic Twin Head Bottle Air Jet Cleaning Machine



[Layout](#)



[E-Catalog](#)



[Video](#)

The Automatic Twin Head Air Jet Cleaning Machine Model BAVC-60 with speed of Max. 60 bottles per minute.

The AirJet Cleaning Machine applies Compressed Air through Jets and also sucks through Vacuum. Machine can be used to clean Glass/Plastic/PET Bottles, Jars etc. Machine suitable for cleaning of non-sterile products like Dry Syrups, and Bulk Packing of Tablets and Capsules.

Machine with built-in Turn Table which feeds container in vertical position through conveyor to cleaning station, where cleaning heads grip the container through cup holder and starts the Compressed Air and then Vacuum to clean the bottles.

Machine in Stainless Steel Finish with all contact parts in Ss316 and Nylon Materials. Machine also having overload clutch system to prevent jamming during the operation. The manifold comprises of inner nozzles which jets compressed air in the bottle and an outer socket, which cover the mouth of the bottle and is connected to an exhaust, ensures perfect cleaning.



SPECIAL FEATURES :

- No Container - No Air - No Vacuum System
- Two Air Jet Nozzle with Vacuum Mouth Holder for Cleaning
- Fully Stainless Steel Finish
- Simple Change over for different size - Only Mouth Holder required
- Complete operation in Vertical position
- Overload Clutch for Jamming
- Optional A.C. Variable Frequency Drive System.
- Automatic Infeed and Outfeed of containers
- Intermittent Linear Motion of Machine

TECHNICAL SPECIFICATIONS : Model BAVC-60 /100

Product Diameter :	Upto 90 mm*
Product Height :	150 mm*
Electrical :	415VAC Three Phase Power Supply (50 Hz) and 220 VAC 1 Phase Power Supply
Power :	2.0 H.P.
Speed :	Upto 60 per minute depending on bottle size
Compressed Air Consumption :	40cfm to be provided by customer
Vacuum Pump/Line :	300 Ltr. Capacity to be provided by customer
Conveyor Height :	875 to 950mm Adjustable
Overall Dimensions :	2400 mm (L) x 775 mm (W) x 1300 mm (H)

* Specification can be changed as per customers requirements